

BRETFORD BASICS™ ADJUSTABLE PROJECTOR CART

5

A2642NS

Adjusting to multiple heights is as simple as resetting four screws. Pull out notebook shelf and open, roomy shelves provide ample storage space.





Now available with a new and improved 6-outlet power strip!





FEATURES

- · Incorporates your laptop, data projector, DVD player, scanner and more all on one compact presentation cart.
- Features a 5-height capability, from 26-42"h in 4" increments and is easily adjusted by resetting four leg screws.
- Large 14"d notebook shelf pulls out on smooth rolling glides and allows you to easily integrate your notebook computer with projectors and other equipment.
- · Notebook shelf supports are arc welded to the leg supports for a strong and secure platform to support expensive computer equipment.
- Durable all-steel construction with black powder paint finish feature legs welded to the shelves so minimal assembly time is required.
- Rolls smoothly on 4" "Quiet Glide" casters, 2 locking.
- Die-pressed shelves have a 1/4" lip to prevent equipment from accidentally sliding off while in transport.
- Top shelf includes a ribbed rubber mat.
- Recommended for use with a projector and notebook computer or up to a 20" diagonal monitor.
- New and improved 6-outlet electrical unit available with built-in cord winder and 20' extension cord. Lets you set up anywhere in the room and still reach an electrical outlet. Electrical units are standard on A2642NS "E" and "M" models.
- A2642NS series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. A2642NS series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.

6





Top Shelf: 24"w x 18"d

Notebook Shelf: 20"w x 14"d, supports up to 15 lbs.

Notebook Shelf Height Clearance: 2-1/2"h

Middle to Notebook Shelf: 1"-13"h Bottom to Middle shelf: 15-1/2"

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 15 lbs.

NOTE: The pull out shelf has been designed for use with a notebook computer and like items. Objects greater than 15 lbs should not be used on the pull out shelf as it may cause a tip hazard when the shelf is extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (BK) powder paint

STANDARD EQUIPMENT

24"W x 18"D Shelves (3)

20"w x 14"d Notebook Shelf (1)

14" Glides (1 set)

1" round plastic caster insert (4)

4" diameter casters (4)

18" x 24" Rubber Mat (1)

6-outlet electrical unit (1) [A2642NS "E" and "M" models only]

WEIGHT AND FREIGHT CLASS



A2642NSE: 47 lbs. A2642NSE: 49 lbs. A2642NS-M4: 49 lbs.

Freight class 85. All available to ship via UPS Ships ready to assemble in one (1) carton pack

ACCESSORIES

E6 Electrical assembly with 6 grounded outlets, 20 ft.

grounded extension cord. [Standard on A2642NS "E" and

"M" models.]

4" CASTER CART CARTON DIMS & UPC CODE

26"w x 20"d x 32"h

A2642NS: 0 96633 30471 4 A2642NSE: 0 96633 30535 3 A2642NS-M4: 0 96633 30473 8

5" CASTER CART CARTON DIMS & UPC CODE

26"w x 20"d x 32"h

A2642NS-P5: 0 96633 30474 5 A2642NS-E5: 0 96633 30475 2 A2642NS-M5: 0 96633 30476 9



The A2642NS adjustable cart is made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The A2642NS adjustable carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. A2642NS series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

SUGGESTED SPECIFICATIONS

Adjustable Table has three (3) 20-gauge steel 18" x 24" shelves. Each shelf is press formed with a 1/4" lip bordering the top surface on all four sides to prevent equipment from sliding off. The top shelf has a 20-gauge steel stiffener electrically welded underneath the surface front to back. A Black rubber 18" x 24" mat is placed on the top shelf. A 14" X 20" pull out notebook shelf pulls out from under the top shelf on 14" glides. The pull out shelf is mounted to two steel bars that are arc welded between the leg posts on the upper portion of the cart and safely supports equipment up to 15 lbs. The top and middle shelves have two (2) 3/16" diameter holes centered on both the right side and the left side to accept an optional electrical assembly. The table has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs 21-1/4" long welded to the shelf at each corner. Each offset leg has two (2) 1/4" diameter holes near the bottom of the section and in the center of the leg that will accept a 1/4-20 machine screw. The holes are spaced 4" apart to permit height adjustments of 26", 30", 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by a machine screw. The bottom section of the adjustable table consists of two (2) 20-gauge steel 18" x 24" shelves - one at the top of the section and the other at the bottom. There are four (4) 14gauge steel 19" legs welded to the shelves at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg that will accept a 1/4-20 machine screw. Holes are 4" apart to permit table height adjustments (as noted above). Model has a black powder paint finish. A hard plastic caster insert is mounted to each leg. Casters are mar- resistant Black hard rubber and 4" in diameter. Each caster assembly has ball bearing swivel capabilities and steel construction, two (2) have locking brakes. 4" stem casters are load rated for 115 lbs. each. Optional electrical assembly provides six (6) grounded outlets with surge suppression. Includes 20 ft., 3-wire cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. The A2642NS Projector Cart ships assembled in one (1) carton and is able to ship via UPS.



5