

# Seattle X22N

## Specifications



### BRIGHTNESS

2200 Lumens (Standard)

1650 Lumens (Economy)

### RESOLUTION

1024x768 XGA (Native)

1600x1200 UXGA (Compatible)

### DISPLAY TYPE

0.63" LCD w/ MLA x 3

### CONTRAST RATIO

500 :1

### ASPECT RATIO

4:3 Native

16:9 Compatible

### THROW RATIO

1.45 ~ 1.73 (x screen width)

### PROJECTION LENS

Manual Zoom & Focus

### ZOOM RATIO

1.2:1

### DIAGONAL IMAGE SIZE

40" - 300"

### THROW DISTANCE

3.33' - 25' Feet

### KEystone

+/- 30° Vertical

### LAMP

200 watt UHP

### LAMP LIFE

3000 (Standard)

5000 (Economy)

### INPUTS

VGA

DVI-I

Composite

S-Video

Component RCA Audio (R/L)

Audio x 2 (3.5mm)

### OUTPUTS

VGA

Audio (3.5mm)

### PROJECTOR CONTROLS

USB

RS232 (9-pin)

RJ45 LAN Connection

### COMPATIBILITY

VGA, SVGA, XGA, SXGA, UXGA, Mac

### EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

### FCC CERTIFICATION

FCC-B, UL, cUL, TUV, CD, CE, CCC

### VIDEO COMPATIBILITY

NTSC, NTSC 4.43, PAL M/N 60, SECAM

### AUDIO

1 x 8w Mono Speaker

### DECIBEL RATING

33 dB (standard) / 30 dB (economy)

### H-REFRESH RATE

31-92 kHz

### V-REFRESH RATE

48-120 Hz

### POWER SUPPLY

AC 110 ~ 240 Volts

50-60Hz (auto ranging)

### POWER CONSUMPTION

285 Watts (standard)

<5w standby

### DIMENSIONS (WxDxH)

12.8" x 10.24" x 3.8" Inches

### WEIGHT

7.3 Lbs

### WARRANTY

3 year parts & labor / 90 day lamp

### Special features of the Seattle X22N include:

**LAN Connectivity**— For network installation. Manage your projectors through a web-based platform.

**Quick Start Up and Shut Down**— Start presenting quickly and only a 10 second cool down cycle when you finish!

**Side Changing Lamp and Filter**— Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.

Throw Distance (ft)

