

3M™ Overhead Projector 1600 Series



technical data

(Small)
meeting rooms

(Small to Medium)
meeting rooms

Product Reference	1608	1620	1650
Type of Projector	Transmissive	Transmissive	Transmissive
Lens Type	Singlet	Triplet	Triplet
Lens Focal Length	11.2"	13"	13"
Lamp changer	Yes	Yes	Yes
Lamp Type	EHJ (24v/250w)	EHJ (24v/250w)	EHJ (24v/250w)
Light Output (Lumens)	2000	2100	3400
Fold down arm	Yes	Yes	Yes
Stage Aperture	11.25" x 11.25"	11.25" x 11.25"	11.25" x 11.25"
Dimensions (W x D)	13.5" x 13.5"	13.5" x 13.5"	13.5" x 13.5"
Weight	30 lb	30 lb	30 lb
Voltage rating	120Vac,60 Hz	120Vac,60 Hz	120Vac,60 Hz
Powercord Length	10 ft.	10 ft.	10 ft.
Agency Approval	UL/cUL	UL/cUL	UL/cUL

3M™ Overhead Projector 2000 Series



technical data

(**Small**)
meeting rooms

(**Small to Medium**)
meeting rooms

Product Reference	2000	2660
Type of Projector	Reflective	Reflective
Lens Type	Singlet	Triplet varifocal
Lens Focal Length	11.5"	10.6 - 11.7"
Lamp changer with extra lamp	No	Yes
Lamp Type & reference	82V-250W EVW	24V-275W FNT
Light Output (Lumens)	1600	2500
Fold down arm	Yes	Yes
Stage Aperture	10.5 x 10.5"	11.25" x 11.25"
Dimensions (W x D)	13" x 19"	12.5" x 16.5"
Weight	14 lbs	11 lbs
Fan Noise	n/a	40 dB
Voltage rating	120Vac,60 Hz	120Vac,60 Hz
Powercord Length	10 ft.	10 ft.
Agency Approval	UL/cUL	UL/cUL