

# PTZ OPTICS PT-610



**Touchboards**  
 205 Westwood Ave, Long Branch, NJ 07740  
 Phone: 866-94 BOARDS (26273) / (732)-222-1511  
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



## PTZ OPTICS Broadcast PTZ Camera Controller

The PTZ Optics PT-610 is a portable broadcast camera control system that supports Sony, Panasonic, Canon and other broadcast-handheld camcorders providing remote control. Achieve full speed PTZ Control with intelligent soft start and stop control. Feel safe with our built-in voltage control regulator for power protection.

### KEY FEATURES

- Supports Sony, Panasonic, Canon Cameras
- Supports VISCA, Pelco P & Pelco D control protocols
- Full speed PTZ Control, with intelligent start/stop
- Up to 255 Presets
- Supports Ceiling Mounting

### WHAT'S IN THE BOX

- PT-610 Portable Camera Controller
- Power Supply
- Instruction Manual

#### Supports Camera Types

Supported Camera Types: EX serial models, including Sony: PMW-EX1(R), PMW-EX280, PMW-EX260, etc.  
 P serial models, including Panasonic: AJ-PX285MC, AG-HPX265MC, AG-HPX173MC, etc.  
 L serial Sony: HXR-NX5C, HVR-Z5C, HXR-NX70C, etc. Canon: XF100, XF200, XF300, XA-20, XA-25, etc. JVC: GY-HM600EC, GY-HM650EC, etc.

Supported Controllers: Panasonic Controllers: AW-RP605, AW-RP555MC, AW-RP655MC. Sony Controllers: RM-BR3000 and switcher with control functions (such as AWS-G500). VISCA Protocol Controller, Pelco-P/D Controller

#### Pan & Tilt Movement

Rotation Range	340°
Rotation Speed	Level: .01 ~25°/S; Vertical: 0.1~20°/S
Presets	255 Presets

#### Additional Support

Remote Switch	Supported
Power Supply Module	Supported
External Power Supply	Supported
Decoder	Built-in higher performance de-coder
Controller Distance	No longer than 1200 Meters
Max Load	Side Load: 11lbs Top Load: 6lbs
Control Interface	RS-485, RS-422

#### Electrical Index

Power Supply	15W Consumption (w/o camera)
Input Voltage	AC/DC 15~24 (3 A)

#### Physical Specifications

Dimensions	6.2" x 5.9" x 10.6"
Weight	8.8 lbs.