

Highlights

Safe & Secure

- Tested and certified to UL 60950-1 standards, FCC requirements and all applicable countryspecific regulations
- Six-point lock assembly provides strong theft deterrence; includes security screws to attach product to the wall
- Fan and ventilation system maintains safe operating temperature
- Ergotron not only uses UL-certified components, but goes a step further to have UL certify the entire system to guarantee safe use within the classroom, healthcare, or enterprise setting

Top-rated Sync & Charge

- Built-in syncing capability; simultaneously sync up to 10 devices by connecting your laptop via the cabinet's USB port
- Full 2.1A charging capability

Slim & Open Design

- Fits most anywhere: very low profile only 4"
 (10 cm) deep, even with access doors
- Accommodates most iPad cases including the popular Otterbox Defender™ and Griffin Survivor™

Easy Set-up & Operation

- Choose pre-installed 30-pin or pre-installed Lightning™ cable option
- Quick, simple installation includes mounting template
- Patent-pending Show & Stow™ technology extends iPad devices to the user when the door is opened for easy storage and removal
- Easy to clean, sleek and smart design hides device and cord clutter
- Clear ISI (Individual Status Indicator) LEDs provide power and charging status of each individual device at a glance



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Ergotron®

Tablet Management Wall Mount 10, for iPad®



Ready. Set. Charge.

Sleek, low-profile design accommodates the Apple® iPad, iPad mini and iPod® touch. Durable steel doors with robust six-point lock and key assembly provide strong theft deterrence. Full 2.1A charging capability. Tested and certified to UL 60950-1 standards.





- Compact Size: 23.2"W x 31.8"H x 4.0"D (59 x 80,9 x 10,2 cm)
- Easy installation:
 - 1. Mount two brackets on the wall using installation template
 - 2. Hang wall mount unit
 - 3. Secure to wall with security screws
 - 4. Install power cord cover
 - 5. Plug iPad devices into unit
 - 6. Plug Tablet Management Wall Mount into the wall outlet
- Includes external USB 2.0B port to connect laptop for syncing (USB cable not included)
- Cooling/ventilation: one 5V DC continuous operation fan
- Power system: input: 100-240V~, 2.0A, 50/60 Hz
- Temperature range:

Operating 0° to 30°C (32° to 86°F) Storage -40°C to 60°C (-40° to 140°F)

Relative humidity (maximum):

Operating 10-90% (non-condensing) Storage 5-95% (non-condensing)

- Altitude (maximum): 2000 m (6,562 feet)
- Environmentally clean: RoHS, REACH, WEEE and EU (94/62/EC) packaging compliant
- Entire system certified to UL 60950-1 and UL 2442. Complies with FCC Part 15 Class A requirements







TABLET CASES - The following iPad 2/iPad (3rd generation)/iPad (4th generation) cases are tested and confirmed to work with the Tablet Management Wall Mount: Apple iPad Smart Case, Belkin Protective Case with Stand, Belkin Tri-Fold Folio, Belkin Snap Shield, Brenthaven Bionic, Casecrown Trifold Case, Casecrown Omni, Griffin Intellicase, Griffin Survivor, Gumdrop Drop Tech, Hard Candy Street Skin, Logiix Roadster II, Otterbox Defender Series (without separate top cover), Otterbox Reflex Series, Speck FitFolio, STM Skinny 3, STM Grip, Targus SafePort Rugged and Rugged Max Pro, Targus Slim Case, Targus Versavu, Trident Aegis, Trident Kraken AMS









Tablet Management Wall Mount 10 For 30-Pin iPad

(silver/black) US/Canada/Mexico DM10-1001-1 EU DM10-1001-2 UK/SING/HK DM10-1001-3 AU/NZ DM10-1001-4 China DM10-1001-5 Japan DM10-1001-6



Tablet Management Wall Mount 10 For Lightning iPad

(silver/black) US/Canada/Mexico DM10-1002-1 EU DM10-1002-2 UK/SING/HK DM10-1002-3 AU/NZ DM10-1002-4 China DM10-1002-5 Japan DM10-1002-6

Part # (color)

Tablet Management Wall Mount unit, 6 foot power cord, 10 charging cables (30-pin or Lightning option), external USB 2.0B port for connecting laptop, power cord cover, 2 wall mount brackets and associated hardware for installation on wood stud or concrete walls,

	installation template, security allen wrench, 90 degree Phillips wrench	
Cables	30-pin	Lightning
Charge	2.1A	2.1A
Compatible Devices (most cases fit)	iPhone 4S iPhone 3GS iPod touch (4th generation) iPod touch (3rd generation) iPad (3rd generation) iPad 2 iPad	iPhone 5 iPod touch (5th generation) iPad mini iPad (4th generation)
UL Certification	Yes	Yes
Maximum Dimensions Individual Tablet (including cover)	\leq 10.2"H x 7.9"W x 0.9"D (25,9 x 20,1 x 2,3 cm)	≤ 10.2"H x 7.9"W x 0.9"D (25,9 x 20,1 x 2,3 cm)
Weight Capacity	24 lbs (11 kg) 2.4 lbs (1,1 kg) per device	24 lbs (11 kg) 2.4 lbs (1,1 kg) per device
Shipping Dimensions	36.5" x 26.4" x 7.0" (92,6 x 67 x 17,7 cm)	36.5" x 26.4" x 7.0" (92,6 x 67 x 17,7 cm)
Shipping Weight	39.5 lb (17,9 kg)	39.5 lb (17,9 kg)
Warranty	Five (5) years workmanship/mechanical components, two (2) years on power module, one (1) year on electrical components	

© 2013 Ergotron, Inc. rev. 05/07/2013/EA Literature made in US Content is subject to change without notification



