

Huge brightness for an unbelievable low price

Do you need high brightness but only minimal money to spend? The InFocus IN120 Series has you covered. These are the lowest-cost projectors we offer at this high brightness.

These value-packed projectors are easy to buy and built to perform. In addition to high brightness, they have an HDMI input, a high contrast ratio, BrilliantColor™ technology, and a slim, lightweight design that makes them easy to move or install.

Why choose the IN120 Series?

- Ultra-low purchase price
- High brightness of up to 3200 lumens
- High 4000:1 contrast ratio
- Slim design and weighs only 4.8 lbs (2.17 kg)
- Accurate and vivid color reproduction with BrilliantColor technology
- HDMI connectivity
- 3D technology supports up to 120 Hz frame rate

Low Total Cost of Ownership

The IN120 Series has not only a ultra-low purchase price, but also a long-lasting lamp that lowers total cost of ownership even further. There aren't even any filters to replace. It's an unbeatable value.

High Brightness and High Contrast

The image quality of these projectors will not disappoint. 3200 lumens will give you bright, clear images with the lights on and the high 4000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface.



MODELS

IN122

SVGA
(800 x 600)
3200 lumens
HDMI 1.4

IN124

XGA
(1024 x 768)
3200 lumens
HDMI 1.4

IN126

WXGA
(1280 x 800)
3200 lumens
HDMI 1.4



Connectivity

VGA x 2	HDMI 1.4
Composite Video	S-Video
RS232	3.5 mm audio in
Mini USB	3.5 mm audio out
(control & firmware)	Monitor out (VGA)

Resolution Options

Choose from native resolution of SVGA for the best price, XGA for better image detail and clarity, or widescreen WXGA resolution for projecting high definition video and wide laptop screens without scaling.

Compact, Slim and Light

The IN120 Series is small and lightweight for easy portability from one room or building to the next. It's slim design is only 2.7 in (70 mm) tall and weighs only 4.8 lbs (2.17 kg).

Specifications*

	IN122	IN124	IN126
Native Resolution	SVGA 800 x 600	XGA 1024 x 768	WXGA 1280 X 800
Maximum Resolution	WUXGA 1920 x 1200		
Display Technology	0.55" SVGA, 800x600 (450 type), DDP2431+DDRII	0.55" XGA, 1024x768 (450 type), DDP2431+DDRII	0.65" WXGA, 1280x800 (450 type), DDP2431+DDRII
Brightness	3200 lumens Normal Mode (2500 lumens Eco Mode)		
Lamp Life**	3500 hours Normal Mode (5000 hours Eco Mode)		
Lamp Power	230W UHP		
Contrast Ratio	4000:1		
Color Wheel	6 segment, 2x speed		
Audible Noise	30 dB Normal Mode (28 dB Eco Mode)		
Computer Compatibility	PC, MAC		
Projection Offset	15%		13%
Keystone Correction	+/- 40% vertical		
Lens Type	Manual zoom and focus		
Lens - Throw Ratio	1.97 - 2.17 (50"@ 2 m)		1.47 - 1.83 (99.6"@ 3.2 m)
Lens - Zoom Ratio	1.1:1		1.2:1
Number of Colors	1.07 billion		
Aspect Ratio	4:3 (Native), Supports 16:9, 16:10, Auto		16:10 (Native), Supports 4:3, 16:9, Auto
Synch - Horizontal Scan Freq	31 - 100 kHz		
Synch - Vertical Scan Freq	50 - 120 Hz		
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)		
Audio	2 W mono		
Input Sources	HDMI 1.4, VGA x 2, Composite Video, S-Video, 3.5 mm stereo input, RS232C, USB B Mini (control & firmware)		
Output Sources	Monitor out (VGA), Audio out (3.5 mm)		
Control	Projector Keypad, IR Remote, RS232, USB B Mini for mouse		
Product Dimensions - WxDxH	11.81 x 9.25 x 2.76 in / 284 x 235 x 70 mm		
Product Weight	4.8 lbs / 2.17 kg (Estimated)		
Shipping Dimensions - WxDxH	12.99 x 12.99 x 5.90 in / 330 x 330 x 150 mm		
Shipping Weight	8.0 lbs / 3.67 kg (Estimated)		
Maximum Altitude	10,000 ft / 3,048 m		
Operating Temperature	41 - 95° F / 5 - 35° C		
Remote Control	Full function (no laser)		
Security Features	Security lock slot, Security bar, User PIN		
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control		
Warranty	5 years parts ¹ , 2 years labor ²		
Lamp Warranty	6 months		
Accessories Warranty	90 days		
Menu Languages	19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)		
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe)		

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

Optional Accessories

Replacement Lamp (SP-LAMP-070)
 Universal Ceiling Mount (PRJ-MNT-UNIV)
 LiteShow Wireless Adapter (INLITESHOW3)
 LiteShow Mount (PRJ-MNT-LS3)
 Soft Carry Case (CA-SOFTCASE-MTG)
 Cables and adapters
 Extended warranties

Warranty

Providing the highest quality products and support is very important to us. The IN120 Series comes standard with a 5-year limited factory warranty (including parts¹ and labor²), 6-month limited lamp replacement warranty, and 5-year DLP® warranty. Extended product and lamp warranty programs are also available.



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

©2012 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies.

¹Excludes power supply, fans, color wheel and light tunnel which are covered for two (2) years. ²Labor is covered for two (2) years from date of proof of purchase. InFocus_IN120_Series_DS_EN_22JUL12.

InFocus

Bright Ideas Made Brilliant

www.infocus.com